## **ADP90DC Series**

Single Output Adapter





## Features:

- 90W Max. Continuous Output Power
- 4.6"  $\times$  2.1"  $\times$  1.3" Package Size
- Low Output Ripple and Noise
- OVP, OCP, OTP and Short Circuit Protection
- Reverse Polarity Protection
- Built-in EMC Filter
- Safety Approvals (A)

All specifications are typical at nominal input, full load at 25 °C unless otherwise stated.				
Electrical Specs			General	
INPUT Input Range Input Current Efficiency Shutdown Current UVP Protection	10 ~ 28V DC 11A max.@10V DC, full load >84% @full load, input 10V DC Less than 100mA until start-up Between 8V ~ 9V	Switching Freq. Isolation Voltage Weight MTBF Warranty Into	100KHz fixed 2150 Vdc 0.525Kg (1.157 lbs.) max Upon request 1 year	
Reverse Polarity	Protection and not damage			
			Environmental	
OUTPUT Maximum Power Output Voltage Voltage Regulation Output Current Noise & Ripple Capacitive Load Hold-up Time Power On Time OVP Protection Short Protection	70W Continuous 12.6V ±0.5V As defined in output voltage Max. Load 5.6A Peak Load 7A @ 5 second duration both modes 120mV pk-pk max. 2200uF for system > 5ms @ Full load and 12V DC 3S max. @ 10VDC shall not exceed 16 volts Auto-restart mode	Operating Temp Storage Temp Temp. Derating Relative Humidity Vibration Shock RoHS	5°C~40°C -20°C~85°C Decrease to 66% load from 40°C to 80°C 5%~95% RH non-condensing 1.5G, 5~500Hz @ three orthogonal axes Per MIL-STD-810E part IV Compliant	
OCP Protection	8A Maximum		EMC	
CE EN55024,EN550	Safety 022,EN61000	Conducted Emissions Radiated Emissions	EN55022, Class B EN55022, Class A	

 $\ensuremath{\textbf{A}}$  . We will offer the safety certificate, according to the customer's request.

Amperor Inc. 11320 Neeshaw Dr. Houston, TX 77065 1-281-807-3320 http://www.amperor.com Amperor Europe Ltd. 30 Ballot Road Irvine KA12 OHW Scotiand U.K 44-(0)-1294-272400

Intertek Corp, an Amperor Company 4th, FI, Far East World Centre Hsin Tai Wu Road, Hsin-Chih, Taipei,Taiwan R.O.C 886-2-2698-2239



## **Mechanical Information**





Figure 1: For ADP90DC-125521 and ADP90DC-125525 Model

Figure 2: For ADP90DC-125521U and ADP90DC-125525U Model



Note:

- 1. For the ADP90DC series model, only a cigar plug and output plug specification is different.
- 2. All dimensions in mm(inch)
- 3. Detailed mechanical drawing upon request

## DataSheet @ Amperor, Inc. @ 2008

The information and specifications contained in this datasheet are believed to be accurate at time of publication.

Specifications are subject to change without notice.